

Strong Room Doors



Vault Door



Strong Room Door with Grille Gate

Product Dimensions

MODEL	BRD 06	BRD 09	BRD 12	BRD 25
Clear Opening		1908mm(H) X 805mm(W)		
Overall Frame		1996mm(H) X 1005mm(W)		
Overall Door Thickness		100mm		
Protective Thickness	6.0 mm	9.0 mm	12.00 mm	25.0 mm
Barrier Material		Harden plate		
Front Bolts		4 moving horizontal bolts (25mm diameter)		
Rear Bolts		4 fixed horizontal bolts (25mm diameter)		
Locking : KCL		3-wheel combination		
Locking : KL		Seven-lever industrial lock - 2 X 160mm key		
Relockers	NONE	ONE	TWO	TWO
Steel encased fire resisting chamber		25.0 mm		
Hinge		Heavy Duty Bearing Hinges - Left/ Right hung		
Back Panel		With hinges and secured by 2 X camlock		
Handle		Iron - cast handle		
Finish		Painted finished		
Grille Gate		Optional (painted)		
Grille Gate Locking		2 X Dead bolt lock		
Net Weight	280KG	350KG	400KG	580KG
Standard Wall Thickness		250mm		

P.O.BOX: 33246 / 00600
 Twiga Towers, Ground floor,
 Opp. Meridian Court Hotel, Off Moi Avenue,
 Nairobi, Kenya
 Cell: 0757 694 850 / 0723 603 636
 Email: sales@interplussafes.co.ke
 Web: www.interplussafes.co.ke